



Technical Specification		
BS 8442:2015	Clause	Notes
RSRB Type:	13.1.1	Type A
Design:	13.1.2	Compliant
Height:	13.1.3	931mm
Body:	13.1.4	Compliant
Projected Area (Front):	13.1.5	212280mm ²
Projected Area (Side):	13.1.5	22270mm ²
Chromaticity:	13.2.1	Compliant
Photometric Performance	13.2.2	R3B
Adhesion to Substrate	13.3.1	Compliant
Corrosion Resistance (Body)	13.3.2	SP2
Corrosion Resistance (Fixings)	13.3.2	SP1

Additional Information

*5 year materials and workmanship warranty

Passively Safe: Passed BS EN 12767:2007 impact testing with a rating of 50/NE/4

Recessed panels to give added protection on impact

Made from 100% recyclable materials (excluding retroreflective panels)

Options

Double aspect signage available (rear reflective panels)

Available in either black or white

Range of fixing options available

Tamperproof fixing option available on request

Reduced Replacement cost

Quick and easy replacement of bollard top via a single attachment bolt.

Reduces replacement cost by 30%

Standard sign aspect variants



D610



D610 Turn left

Turn right

* 5 year warranty subject to terms and conditions, contact Pudsey Diamond Engineering for details



Plain / opal



D955 Cycle only





NOTES: (1) ALL DIMENSIONS IN mm. (2) REMOVE ALL BURRS AND SHARP EDGES.

2017 PUDSEY DIAMOND ENGINEERING LTD. ALL RIGHTS RESERVED. THIS DOCUMENT OR ANY PART THEREOF MAY NOT BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY WAY WITHOUT WRITTEN PERMISSION FROM PUDSEY DIAMOND ENGINEERING LTD. MATERIAL:

SEE NOTES

LINEAR TOLERANCES UNLESS OTHERWISE STATED: ANGULAR TOLERANCES UNLESS OTHERWISE STATED $X.00° = \pm 0.15°$ $X.00 = \pm 0.15$ X.0° = ±0.50° $X.0 = \pm 0.50$ $X = \pm 5.00$ $X^{\circ} = \pm 1.00^{\circ}$ DATE:

SCALE: 06/01/16

FAX: 01264 336688

TEL: 01264 336677

E-MAIL: SALES@PUDSEYDIAMOND.COM

SPEC:

FINISH:

DRAWN: CHECKED: 3RD ANGLE

WEBSITE: WWW.PUDSEYDIAMOND.COM