Glowb Cl Our baselit RSRB Illuminate / De-illuminate? We've got it covered





Glowb⊘ll™

Key Features

- **Base lit** Retrofittable to existing base light installations.
- Adaptable will act as a reflective bollard when not lit.
- Retroreflective panels gives excellent visibility day or night.
- **Regulations** Designed to BS EN 12899-2: 2007 / BS 8442:2015
- **Reliable** Moulded from a highly durable & exceptionally strong grade of polyethylene.

Additional Features

- **270mm Signface** Range of standard signfaces available.
- **Recessed panels** Added protection against vandalism and weathering.
- **Double aspect** Reflective panels can be fitted to both front and back of the bollard.
- Low Maintenance smooth finish allows for easy cleaning.
- **Consistency** Designed to sit alongside Pudsey Diamond, Visaboll[™], Solaboll[™] & Powaboll[™] to give a uniform street scene.
- **Flexible** The flexible material used ensures the bollard will always stand upright, even after multiple impacts

Dimensions	
Overall height	916mm
Bollard width (max)	395mm
Bollard depth (max)	180mm
Fixing centres	228 x 228mm
Signface	270mm Diameter
Front reflective area	162,500mm ²
Side reflective area	58,500mm ²

Address: Pudsey Diamond Engineering Mitchell Close West Portway Industrial Estate Andover ,Hampshire SP10 3TJ Contact: Tel: 01264 33 66 77 E-mail: sales@pudseydiamond.com



