

## Varoptic™ Datasheet (6 Mantle)

### 72W – 3000K – 70 CRI

Description		Value	Unit
<b>Product Characteristics</b>			
Pudsey Diamond Engineering Reference		6 LED module – 900007202-6	
Classification		Class 1	
Design attitude (operating position)		0°	Degrees
Weight <sup>1</sup>		4.9	Kg
Rated Ambient Temperature		25	°C
Rated Luminaire Efficacy		78.1	lm/W
Driver Model	Philips Xitanium LED Xtreme 110W	Xi FP 110W 0.3-1.0A NLD C150 230V C150 sXt	
Control	Preset, DALI, Profile, LineSwitch 3-step, LineSwitch single-step		10 – 100%
<b>Electrical Characteristics</b>			
Rated Voltage		220 – 240	V
Max input Power		78	VA
Max Output Power		72	W
Power Factor		0.99	
Input Frequency		50/60	Hz
Service Type		Normal	
Charge Code (UMSUG)		Lower limit	42 0016 0000 100
		Upper limit	42 0077 0000 100
<b>Optical Characteristics</b>			
LED / Number		CREE XHP-50B / 6	
LED Efficacy		121	Lm/W
Luminaire Lumen Output <sup>2</sup>		5,993	Lm
Correlated Colour Temperature (CCT)		3,000	°K
Colour Rendering Index (CRI)		70	
S/P ratio		1.2	
Photometric Code		827 559	
Lumen Maintenance Factor		L90B10 > 100,000	
LED optics		Pudsey Diamond Mantle	
LED Optics – Material		Photopolymer Resin	
Photometric files		Available on request	

<sup>1</sup> Weight may vary depending on lantern style, contact Pudsey Diamond Engineering Ltd for further info

<sup>2</sup> Lumen output based on Urbis Albany lantern, contact Pudsey Diamond Engineering Ltd for alternative lanterns